

Standard Product Adjustable Table Height Ranges

All dimensions are to the top of the surface.

Animate®	Range	Link Type	Equipment Weight Capacity	Adjustment Speed	Pinch Points
Fixed	29"	No Link	400 lbs	N/A	.125" on each side / 1" at the rear
Pin	22" - 35"	No Link	400 lbs	Maintenance	.125" on each side / 1" at the rear
Crank	22" - 35"	No Link	250 lbs	8.5 turns/inch	.5" on each side / 1" at the rear
Extended Electric	22" - 48"	No Link	150 lbs	1.3"/sec	.5" on each side / 1" at the rear
Standard Electric	25" - 42"	No Link	150 lbs	1.3"/sec	.5" on each side / 1" at the rear

M Collection™	Range	Link Type	Equipment Weight Capacity	Adjustment Speed	Pinch Points
Fixed	29"	No Link	400 lbs	N/A	.125" on each side / 1" at the rear
Pin	22" - 35"	Thin	400 lbs	Maintenance	.125" on each side / 1" at the rear
Top Crank 2-Leg tables	22" - 35"	Thick	250 lbs	6 turns/inch	.5" on each side / 1" at the rear
Front Crank 2-Leg tables	23" - 35"	Thin	250 lbs	11 turns/inch	.5" on each side / 1" at the rear
Top Crank 3-Leg workcenters	23" - 35"	Thin	250 lbs	11 turns/inch	.5" on each side / 1" at the rear
Front Crank 3-Leg workcenters	23" - 35"	Thin	250 lbs	11 turns/inch	.5" on each side / 1" at the rear
Torsion Seated Range	22" - 35"	Thick	170 lbs S/Surface 150lbs D/Surface	Full travel in 2-3 sec with user	.5" on each side / 1" at the rear
Torsion Sit To Stand Range	27" - 45"	Thick	170 lbs S/Surface 150lbs D/Surface	Full travel in 2-3 sec with user	.5" on each side / 1" at the rear
All Electric	25" - 50"	Thin	250 lbs	1.5"/sec	.5" on each side / 1" at the rear

Marker Collection™	Range	Link Type	Equipment Weight Capacity	Adjustment Speed	Pinch Points
Electric	25" - 51"	No Link	Joined - 150 lbs	1.5"/sec	N/A
Electric	25" - 51"	No Link	Pivot - 75 lbs	1.5"/sec	N/A
Pneumatic	27" - 47"	No Link	Pivot - 25 lbs		N/A

MoveIt™	Range	Link Type	Equipment Weight Capacity	Adjustment Speed	Pinch Points
Electric	22" - 48"	No Link	150 lbs	1.3"/sec	.5" on each side / 1" at the rear

NEXT®	Range	Link Type	Equipment Weight Capacity	Adjustment Speed	Pinch Points
Fixed	29"	No Link	400 lbs	N/A	.125" on each side / 1" at the rear
Pin	26" - 42"	No Link	400 lbs	Maintenance	.125" on each side / 1" at the rear
Top Crank Seated Range	22" - 34"	No Link	250 lbs	8.5 turns/inch	.5" on each side / 1" at the rear
Top Crank Sit To Stand	26" - 42"	No Link	250 lbs	8.5 turns/inch	.5" on each side / 1" at the rear
Front Crank Seated Range	22" - 34"	No Link	250 lbs	11 turns/inch	.5" on each side / 1" at the rear
Front Crank Sit To Stand	26" - 42"	No Link	250 lbs	11 turns/inch	.5" on each side / 1" at the rear
Electric	26" - 42"	No Link	250 lbs	1.3"/sec	.5" on each side / 1" at the rear

PR-1™	Range	Link Type	Equipment Weight Capacity	Adjustment Speed	Pinch Points
Electric	24.5" - 50.5"		175 lbs	1.4"/sec	.5" on each side / 1" at the rear

VISO®	Range	Link Type	Equipment Weight Capacity	Adjustment Speed	Pinch Points
Electric	22" - 48"	No Link	250 lbs	1.5"/sec	1" on each side / 1" at the rear
Electric	24" - 50"	No Link	250 lbs	1.5"/sec	1" on each side / 1" at the rear

Zydeco®	Range	Link Type	Equipment Weight Capacity	Adjustment Speed	Pinch Points
Fixed	29"	No Link	400 lbs	N/A	.050" on each side / .050" at the rear
Pin	22" - 35"	Thin	400 lbs	Maintenance	.050" on each side / .050" at the rear
Top Crank 2-Leg	22" - 35"	Thick	250 lbs	6 turns/inch	1" on each side / 1" at the rear
Top Crank 3-Leg	23" - 35"	Thick	250 lbs	6 turns/inch	1" on each side / 1" at the rear
Torsion Seated Range	22" - 35"	Thick	170 lbs S/Surface 150lbs D/Surface	Full travel in 2-3 sec with user	1" on each side / 1" at the rear
Torsion Sit To Stand Range	27" - 45"	Thick	170 lbs S/Surface 150lbs D/Surface	Full travel in 2-3 sec with user	1" on each side / 1" at the rear
All Electric	25" - 50"	Thin	250 lbs	1.5"/sec	1" on each side / 1" at the rear

REVISED: 2017-03-30

GSA Contract # GS-03F-049DA

711-2 Work Surfaces, Work Stations, Computer Furniture & Accessories, Cage Code: 11093